



**INTERLUBE CORPORATION**<sup>TM</sup>  
4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA  
TELEPHONE 513-531-1777 • FAX 513-531-0193  
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

# PSR-A OILS

A premium quality solvent refined oil with an inherently high Viscosity Index. Specially treated with very effective anti wear additive plus rust and oxidation inhibitors.

Developed for use in modern high pressure, high-speed hydraulic systems to insure maximum pump wear protection, and longer life to other components of the hydraulic system.

This oil has many applications including bearing lubrication by continuous use method such as circulating systems, reservoirs or bath oilers, or by any type of once-through appliance.

Also for electric motors, spindles, hydraulic systems, circulating systems where an exceptionally stable oil is desirable, gear boxes not requiring an EP type lubricant and general plant lubrication.

## ENJOY THESE BENEFITS:

- \* Extended equipment life
- \* Reduced maintenance and increased productions due to longer intervals between oil changes
- \* Multi-Use factor reduces inventory and simplifies storage

## ALL GRADES MEET THESE SPECIFICATIONS:

OXIDATION STABILITY	2000+ Hrs, ASTM Test D-943
RUST & CORROSION PROTECTION	Passes ASTM Test D-665 Procedures A & B
ANTI WEAR QUALITY	Vickers Pump Wear Test ASTM D-2882
HIGH VISCOSITY INDEX	95 Min.
ANTI-FOAM TREATED	ASTM D-892

**AVAILABLE IN MANY VISCOSITY GRADES.**