



4646 BAKER AVENUE • CINCINNATI, OHIO 45212-2594 USA  
TELEPHONE 513-531-1777 • FAX 513-531-0193  
SALES@INTERLUBECORPORATION.COM • WWW.INTERLUBECORPORATION.COM

## **REFRIGERATION OIL 155 AND 300**

Interlube's Refrigeration Oil 155 and 300 are premium quality refrigeration oils specially refined from carefully selected base stocks to give long, trouble free service. They are designed to lubricate properly under the severe demands of refrigeration systems and have the chemical and thermal stability to assure years of uninterrupted service. They are compatible with, and essentially equal to, the oils originally used by the equipment manufacturers.

### **SPECIAL PROPERTIES**

Low Pour Point & Very Low Wax	To prevent wax type crystal precipitation in evaporator and refrigeration lines.
Balanced Thermal Stability	Eliminates hard carbon deposits on valves and ports.
Excellent Chemical Stability	To resist reaction with refrigerants and compressor components.
High Dielectric Strength	To assure proper insulating properties.
No Contaminants	To assure long compressor life.
Compatible with Refrigerants	Freons, ammonia, methylene chloride.

### **TYPICAL PROPERTIES**

	<b><u>REFRIGERATION OIL 155</u></b>	<b><u>REFRIGERATION OIL 300</u></b>
Viscosity SUS @ 100° F	150 - 160	300 - 340
API Gravity	22 - 24	26 - 29
Pour, °F	-40 max	-30 max
Flash, °F	330 min	330 min